

# Material Safety Data Sheet

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II - Europe

Version : 02


Date of revision :

24/07/2019

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

<b>1.1. Product identifier</b>	
	<b>Kinetics Air Bonder 14ml</b> <b>Item: EAB05</b>
<b>1.2. Relevant identified uses of the substance or mixture and uses advised against</b>	
	A non-acid, air-drying bonder formulated for fast, efficient nail preparation, cosmetic Consumer use.
<b>1.3. Details of the supplier of the safety data sheet</b>	
Responsible person:	<b>Kinetics Nail Systems, Ltd</b> 3K Kurzemes pr., Riga, Latvia, LV-1067, Latvia TEL: +(371) 6 7295 260 FAX: +(371) 6 7873 525 e-mail: <a href="mailto:info@kineticsbeauty.com">info@kineticsbeauty.com</a> web: <a href="http://www.kineticsbeauty.com">www.kineticsbeauty.com</a> E-mail of person responsible for Product Safety Data Sheet: <a href="mailto:info@kineticsbeauty.com">info@kineticsbeauty.com</a>
<b>1.4. Emergency telephone number</b>	
	EU:112 Emergency telephone for other regions to be filled out by local business

## SECTION 2: Hazards identification

<b>2.1. Classification of the substance or mixture</b>	
According to regulation (EC) No 1272/2008:	<b>Skin Irrit. 2, H315</b> <b>Skin Sens. 1, H317</b> <b>Eye Irrit. 2, H319</b> <b>Flam. Liq. 2, H225</b> <b>STOT SE 3, H336</b> <b>EUH066</b>
Important adverse physicochemical, human health and environmental effects:	Flam. Liq. 2, Flammable liquids, Hazard Category 2; H225 Highly flammable liquid and vapour. Skin Irrit. 2, Skin corrosion/ irritation, Hazard Category 2; H315 Causes skin irritation. Skin Sens. 1, Sensitisation — Skin, hazard category 1; H317 May cause an allergic skin reaction. Eye Irrit. 2- Serious eye damage/eye irritation: Hazard Category 2; H319 Causes serious eye irritation. STOT SE 3 Specific target organ toxicity — Single exposure, Hazard Category 3, Narcosis; H336 May cause drowsiness or dizziness. EUH066 Repeated exposure may cause skin dryness or cracking.
<b>2.2. Label elements</b>	
According to regulation (EC) No 1272/2008: (Applicable from 01.06.2015)	 <p><b>Danger!</b> H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness EUH066 Repeated exposure may cause skin dryness or cracking. Contains: Ethyl acetate; (1-Methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-</p>

	<p>propanediyl)] bismethacrylate; 2-Hydroxyethyl methacrylate.  P101 If medical advice is needed, have product container or label at hand.  P102 Keep out of reach of children.  P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  No smoking.  P264 Wash hands thoroughly after handling.  P280 Wear protective gloves/protective clothing/eye protection/face protection.  P302+P352+P332+P313+P362+P364 IF ON SKIN: Wash with plenty of water and soap. If skin irritation occurs: Get medical advice/ attention. Take off contaminated clothing and wash it before reuse.  P305 +P351 +P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  P337+P313 If eye irritation persists: Get medical advice/attention.  P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  P312 Call a POISON CENTER or doctor/physician if you feel unwell.</p>
<b>2.3. Other hazards</b>	
	Product does not meet the criteria for PBT or vPvB in accordance with Annex XIII of REACH (Regulation (EC) No 1907/2006).

See section 11 for more detailed information on health effects and symptoms.

### SECTION 3: Composition/information on ingredients

<b>3.1. Substances</b>	No relevant.
<b>3.2. Mixtures</b>	Blend of solvents.

Ingredient name (INCI)	Identifiers:	Conc. %	Classification Regulation (EC) 1272/2008 (CLP)	Type
Ethyl acetate	CAS: 141-78-6 EC: 205-500-4 INDEX: 607-022-00-5	80-85 %	Flam. Liq. 2, H225 EUH066 Eye Irrit. 2, H319 STOT SE 3, H336	[1] [2]
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	CAS: 1565-94-2 EC: 216-367-7 INDEX: N/A	5-10 %	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317	[1]
2-Hydroxyethyl methacrylate	CAS: 868-77-9 EC: 212-782-2 INDEX: 607-124-00-X	5-10 %	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

See section 16 for the full text of the H phrases declared above.

Occupational exposure limits, if available, are listed in section 8.

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] PBT-substance

[4] vPvB-substance

### SECTION 4: First aid measures

<b>4.1. Description of first aid measures</b>	
General advice:	Remove contaminated clothing.
Inhalation:	Remove to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen. Get medical attention.
Skin contact:	Remove contaminated clothing and wash before reuse. Remove and destroy contaminated shoes. Flush with plenty of water. Obtain medical attention if irritation persists.
Eye contact:	Immediately wash the eyes with plenty of water for at least 15 min holding the eye open. Obtain medical attention urgently..
Ingestion:	Do not INDUCE VOMITING. Rinse mouth with water. Get medical attention IMMEDIATELY.
<b>4.2. Most important symptoms and effects, both acute and delayed</b>	

Inhalation:	May cause nose and throat irritation. May affect the brain or nervous system, causing dizziness, headache or nausea. Harmful if inhaled. Narcosis, loss of coordination, vomiting, difficulty with speech, reduced visibility, fatigue, cough, unconsciousness.
Skin contact:	Causes skin irritation. Swelling and redness of skin, dermatitis, drowsiness.
Eye contact:	Cause eye irritation. conjunctivitis, lacrimation, redness and swelling of eyes.
Ingestion:	Harmful if swallowed, abdominal pain
<b>4.3. Indication of any immediate medical attention and special treatment needed</b>	
Specific treatments:	Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

See section 11 for more detailed information on health effects and symptoms.

#### SECTION 5: Firefighting measures

<b>5.1. Extinguishing media</b>	
Suitable extinguishing media:	Foam, extinguishing powder, carbon dioxide, fine water spray.
Unsuitable extinguishing media:	Not known.
<b>5.2. Special hazards arising from the substance or mixture</b>	
	Hazardous combustion products: Oxides of carbon, oxides of nitrogen, irritating organic vapors..
<b>5.3. Advice for firefighters</b>	
	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. During emergency conditions, overexposure to decomposition products may cause a health hazard; symptoms may not be immediately apparent. Obtain medical attention.

#### SECTION 6: Accidental release measures




<b>6.1. Personal precautions, protective equipment and emergency procedures</b>	
	Avoid contact with skin and eyes. Wear protective equipment. Provide adequate ventilation Keep away from heat and sources of ignition.
<b>6.2. Environmental precautions</b>	
	Do not empty into drains / surface water / ground water. Prevent further leakage or spillage.
<b>6.3. Methods and material for containment and cleaning up</b>	
	Soak up with inert absorbent material (e.g. sand, silica gel, universal binder). Keep in suitable, closed containers for disposal. Dispose of in accordance with local regulations.
<b>6.4. Reference to other sections</b>	
	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

#### SECTION 7: Handling and storage

<b>7.1. Precautions for safe handling</b>	
Protective measures:	Avoid inhalation, skin and eye contact.
Advice on general occupational hygiene:	Good industrial hygiene practices should be observed. No smoking. Provide sufficient air exchange and/or exhaust in work rooms. Wash hands before work breaks and after finishing work. Do not eat, drink or smoke while working. Take off all contaminated clothing immediately. See also Section 8 for additional information on hygiene measures.
<b>7.2. Conditions for safe storage, including any incompatibilities</b>	
Storage:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Store in well-ventilated area. Keep containers (solvent resistant) closed when not in use. Store away from ignition sources. All equipment should be grounded. Avoid strong oxidizing agents, store in a clean, dry area. Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see

	section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. Empty container may retain product residues (vapour or liquid).
<b>7.3. Specific end use(s)</b>	
Industrial sector specific solutions:	No applicable.

**SECTION 8: Exposure controls/personal protection**

<b>8.1 Control parameters</b>	
Occupational exposure limits	Limit values are laid down throughout the EU, but each Member State establishes its own national OELs, often going beyond EU legislation. OELs are set by competent national authorities and other relevant institutions. <b>United Kingdom (HSE, 2011):</b> ETHYL ACETATE: Long-term exposure limit, 8-hr TWA reference period: 200ppm. Short-term exposure limit, 15 minute reference period: 400 ppm. ISOPROPYL ALCOHOL Long-term exposure limit, 8-hr TWA reference period: 400ppm/ 999mg/m <sup>3</sup> . Short-term exposure limit, 15 minute reference period: 500ppm/1250mg/m <sup>3</sup> . ISOBUTYL ACETATE Long-term exposure limit, 8-hr TWA reference period: 150ppm/ 724mg/m <sup>3</sup> . Short-term exposure limit, 15 minute reference period: 187ppm/1903mg/m <sup>3</sup> . <b>Latvia (AER, reg.325/2011):</b> ETHYL ACETATE: AER 8 h: 200 mg/m <sup>3</sup> ISOPROPYL ALCOHOL: AER 8 h: 350 mg/m <sup>3</sup> ; 15 min:600 mg/m <sup>3</sup> ISOBUTYL ACETATE: AER 8 h: 200mg/m <sup>3</sup> .
Recommended monitoring Procedures:	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.
<b>8.2 Manufacturer: Exposure controls</b>	
Appropriate engineering Controls:	Ensure good ventilation/extraction.
<b>Individual protection measures:</b>	
Hygiene measures:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.
Respiratory protection	 Ensure adequate ventilation. An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area. Filter type: A
Eye/face protection:	 Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.
Skin protection:	 Chemical-resistant protective gloves (EN 374). Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374): nitrile rubber (NBR; >= 0.4 mm thickness). Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): nitrile rubber (NBR; >= 0.4 mm thickness).

	This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced. Wear suitable protective clothing.
<b>Environmental exposure controls:</b>	
	According to available technology.

## SECTION 9: Physical and chemical properties

<b>9.1 Information on basic physical and chemical properties</b>	
Appearance	
Physical state	Liquid
Colour	Transparent
Odour	Characteristic
Odour threshold	Not applicable.
pH at 25 °C	Not applicable.
Melting point/freezing point	Not available
Initial boiling point and boiling range	Ethyl acetate: 77.1 °C at 101.325 kPa Range: 77°C to 130°C
Flash point	< 10 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	Ethyl Acetate: 11.0/2.2
Vapour pressure	Not available
Vapour density	Not available
Relative density	0.85 – 0.95
Solubility(ies)	Partly soluble in water. Soluble in solvent.
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Evaporation rate	Not available.
Explosive properties	Not available.
Oxidising properties	Not available
<b>9.2. Other information</b>	
Impurity	Not available

## SECTION 10: Stability and reactivity

<b>10.1. Reactivity</b>	
	No hazardous reactions if stored and handled as prescribed/indicated.
<b>10.2. Chemical stability</b>	
	Stable under recommended storage conditions.
<b>10.3. Possibility of hazardous reactions</b>	
	Material WILL NOT undergo hazardous polymerization.
<b>10.4. Conditions to avoid</b>	
	AVOID Heat, sparks, open flame.
<b>10.5. Incompatible materials</b>	
	None if used properly.
<b>10.6. Hazardous decomposition products</b>	
	Various organic compounds.

## SECTION 11: Toxicological information

<b>11.1. Information on toxicological effects</b>				
<b>Product:</b>	ATE mix Oral calculation: >2000 mg/kg, not classified as acute toxic.			
<b>Ingredients:</b>				
<b>Acute toxicity:</b>	<b>Result</b>	<b>Species</b>	<b>Dose</b>	<b>Exposure</b>
ETHYL ACETATE	LD50 Oral	Rat	12.2 mL/kg bw	
	LC50 inhalation	Rat	> 21 mg/L air (analytical)	
	LD50 Dermal	Rabbit	> 16 mL/kg bw	24 h
2-Hydroxyethyl methacrylate	LD50 Oral	Rat	5 564 mg/kg bw	
	LD50 Dermal	Rabbit	> 5 000 mg/kg bw	
<b>Eye irritation:</b>				
ETHYL ACETATE	Irritant			
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	Irritant			
2-Hydroxyethyl methacrylate	Irritant			
<b>Skin irritation/ corrosion:</b>				
ETHYL ACETATE	A 4 -hour occlusive treatment of 6 rabbits with 0.5 mL of the test item similar to OECD TG 404 did not induce any erythema nor edema, therefore the test item does not reveal any irritating potential under the conditions tested (Myers et al., 1987).			
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	Irritant			
2-Hydroxyethyl methacrylate	Irritant			
<b>Sensitisation:</b>				
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	Sensitising to the skin.			
2-Hydroxyethyl methacrylate	Sensitising to the skin.			
<b>Repeated dose toxicity:</b>				
ETHYL ACETATE	NOAEC, inhal.	Rat	500 ppm (2.4 mg/L) Bernard and David, 1996; David et al., 2001).	
<b>Carcinogenicity:</b>	No known effect according to our database.			
<b>Mutagenicity:</b>	No known effect according to our database.			
<b>Toxicity for reproduction:</b>	No known effect according to our database.			
<b>STOT SE:</b>				
ETHYL ACETATE	May cause drowsiness or dizziness			
<b>Potential acute health effects</b>				
Eye contact:	Irritation, conjunctivitis.			
Inhalation:	Irritation, coughing, shortness of breath, narcotic effect.			
Skin contact:	Redness, inflammation. Rash, Urticaria.			
Ingestion:	Gastrointestinal symptoms, such as nausea, vomiting, abdominal pain, and diarrhea could develop.			
<b>Symptoms related to the physical, chemical and toxicological characteristics</b>				
Eye contact:	No specific data.			
Inhalation:	No specific data.			
Skin contact:	No specific data.			
Ingestion:	No specific data.			
<b>Delayed and immediate effects and also chronic effects from short and long term exposure</b>				
<b>Short term exposure:</b>				
Potential immediate effects:	Not available.			
Potential delayed effects:	Not available.			
<b>Long term exposure:</b>				
Potential immediate effects:	Not available.			
Potential delayed effects:	Not available.			
<b>Potential chronic health effects:</b>	Not available.			
<b>Conclusion/Summary</b>				
General	No known significant effects or critical hazards.			
Carcinogenicity	No known significant effects or critical hazards.			
Mutagenicity	No known significant effects or critical hazards.			

Teratogenicity	No known significant effects or critical hazards.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.
<b>11.2. Other information</b>	
	Not available.

**SECTION 12: Ecological information**





<b>12.1. Toxicity</b>						
<b>Aquatic toxicity</b>						
ETHYL ACETATE	Pimephales promelas	freshwater	96 h	LC50	230 mg/L	nominal
<b>12.2. Persistence and degradability</b>						
Readily biodegradable.						
<b>12.3. Bioaccumulative potential</b>						
Low.						
<b>12.4. Mobility in soil</b>						
Not available						
<b>12.5. Results of PBT and vPvB assessment</b>						
Regarding all available data on biotic and abiotic degradation, bioaccumulation and toxicity it can be stated that the substance does not fulfil the PBT criteria (not PBT) and not the vPvB criteria (not vPvB).						
<b>12.6. Other adverse effects</b>						
No known significant effects or critical hazards.						

**SECTION 13: Disposal considerations**

<b>13.1. Waste treatment methods</b>	
<b>Product:</b>	
Methods of disposal:	Waste must be disposed of in accordance with federal, state and local environmental control regulations. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Hazardous waste:	Within the present knowledge of the supplier, this product IS regarded as hazardous waste, as defined by EU regulation 1357/2014
European waste catalogue (EWC):	200113 Solvents
<b>Packaging:</b>	
Methods of disposal:	The generation of waste should be avoided or minimized wherever possible. Packaging: IBC container, plastic drum. Waste packaging should be recycled.
Special precautions:	This material and its container must be disposed of in a safe way.

**SECTION 14: Transport information**

**International transport regulations: Not regulated**

	ADR/RID	ADN	IMDG	IATA
14.1. UN number	1266	1266	1266	1266
14.2. UN proper shipping name	PERFUMERY PRODUCTS with flammable content (ETHYL ACETATE).			
14.3. Transport hazard class(es)				
14.4. Packing group	II	II	II	II
14.5. Environmental hazards	none	none	none	none
14.6. Special precautions for user	Limited quantities: 5L Exempted quantities: Inner package: 30	Limited quantities: 5L Exempted quantities: Inner package: 30	Not viscous product as per IMDG code 2.3.2.5. Limited Quantity: 5l/30kg (gross).	353 (Passenger) - Maximum Quantity 5l 364 (Cargo) - Maximum Quantity

	mL Outer package: 500 mL	mL Outer package: 500 mL	Certified packing: Internal packing metal, glass, plastic. External packing: Cartoon 4G. Flash point : -5°C	60l
14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.			

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU Regulation (EC) No. 1907/2006 (REACH):**

Annex XIV - List of substances subject to authorization:	Substances of very high concern: None of the components are listed.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles:	Not applicable.
<b>15.2. Chemical safety assessment</b>	
Chemical Safety Assessment following regulation 1907/2006/EC:	A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information****Abbreviations and acronyms:**

Full text of abbreviations	CLP: Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008] ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road RID: International Rule for Transport of Dangerous Substances by Railway IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association CAS: Chemical Abstracts Service EINECS: European Inventory of Existing Commercial chemical Substances LC50: Median lethal concentration LD50: Median lethal dose REACH: Registration, Evaluation and Authorisation of Chemicals PBT: Persistent, bio-accumulative and toxic vPvB: Very persistent, very bio-accumulative
Full text of classifications and H statements [CLP/GHS]:	Flam. Liq. 2, Flammable liquids, Hazard Category 2; H225 Highly flammable liquid and vapour. Skin Irrit. 2, Skin corrosion/ irritation, Hazard Category 2; H315 Causes skin irritation. Skin Sens. 1, Sensitisation — Skin, hazard category 1; H317 May cause an allergic skin reaction. Eye Irrit. 2, Serious eye damage/eye irritation: Hazard Category 2; H319 Causes serious eye irritation. STOT SE 3, Specific target organ toxicity — Single exposure, Hazard Category 3, Narcosis H336 May cause drowsiness or dizziness EUH066 Repeated exposure may cause skin dryness or cracking.
Classification system	<b>Classification for health effects:</b> conventional (calculation) method is used. Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319. STOT SE 3, H336 <b>Classification for physico-chemical effects:</b> FLAM. LIQ. 2 H225: Flash point < 23 °C and initial boiling point > 35 °C (Physical data).

	<b>Classification for environmental effects:</b> conventional (calculation) method is used. Not classified.
<b>Training advice:</b>	
	In addition to health, safety and environmental training programs for their workers, companies must ensure that workers read, understand and apply the requirements of this SDS.
<b>Used literature:</b>	
	European Chemical Agency's homepage ( <a href="http://echa.europa.eu/">http://echa.europa.eu/</a> ). Safety data sheets of individual components.
<b>DISCLAIMER OF LIABILITY:</b>	
	The information in this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or method of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS/SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS/SDS information may not be applicable.

**END OF SAFETY DATA SHEET**