

kinetics Material Safety Data Sheet

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II - Europe


Version : 01

Date of revision : 24.01.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
	Kinetics Shield Matt top coat KGPT106
1.2. Relevant identified uses of the substance or mixture and uses advised against	
Identified uses	Cosmetic.
Uses advised against	Manufacture of food products.
1.3. Details of the supplier of the safety data sheet	
Responsible person:	Kinetics Nail Systems, Ltd 3K Kurzemes pr., Riga, Latvia, LV-1067, Latvia TEL: +(371) 6 7295 260 FAX: +(371) 6 7873 525 e-mail: info@kineticsbeauty.com web: www.kineticsbeauty.com E-mail of person responsible for Product Safety Data Sheet: info@kineticsbeauty.com
1.4. Emergency telephone number	
	EU:112 Emergency telephone for other regions to be filled out by local business

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture	
According to regulation (EC) No 1272/2008:	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Aquatic Chronic 3, H412
Important adverse physicochemical, human health and environmental effects:	Skin Irrit. 2, Skin corrosion/ irritation, Hazard Category 2; H315 Causes skin irritation. Skin Sens. 1 - Sensitisation — Skin, Hazard Category 1; H317 May cause an allergic skin reaction Eye Irrit. 2 – Serious eye damage/eye irritation, Hazard Category 2; H319 Causes serious eye irritation. Aquatic Chronic 3 - Chronic Hazard, Category 2; H412 Harmful to aquatic life with long lasting effects.
2.2. Label elements	
According to regulation (EC) No 1272/2008:	 <p>Danger</p> <p>H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H412 Harmful to aquatic life with long lasting effects.</p> <p>Contain: HYDROXYPROPYL METHACRYLATE; TRICYCLODECANEDIMETHANOL DIACRYLATE; ETHYL (2,4,6-TRIMETHYLBENZOYL) PHENYLPHOSPHINATE.</p> <p>P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P103 Read carefully and follow all instructions.</p>

**Kinetics Shield Matt top coat
KGPT106**

	<p>P261 Avoid breathing mist/vapours/ spray. P272 Contaminated work clothing should not be allowed out of the workplace. P264 Wash hands thoroughly after handling. P273 Avoid release to the environment. P280 Wear protective gloves/eye protection. P302+P352 IF ON SKIN: Wash with plenty of water/soap. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/ attention. P501 Dispose of contents/container to in accordance with local/ regional/ national/ international regulation.</p>
--	---

2.3. Other hazards

	Product does not meet the criteria for PBT or vPvB in accordance with Annex XIII of REACH (Regulation (EC) No 1907/2006).
--	---

See section 11 for more detailed information on health effects and symptoms.

SECTION 3: Composition/information on ingredients

3.1. Substances	No relevant.
3.2. Mixtures	Mixture of acrylic monomers and other ingredients.

Ingredient name (INCI)	INDEX	CAS Numbers:	EINECS:	Conc.%	Classification Regulation (EC) 1272/2008 (CLP)	Type
BIS-HPMA POLY(1,4-BUTANEDIOL)-14/IPDI COPOLYMER	N/A	2639188-39-7	N/A	45-55	Skin Irrit. 2, H315 Eye Irrit. 2, H319	
Methacrylic acid, monoester with propane-1,2-diol [HYDROXYPROPYL METHACRYLATE]	N/A	27813-02-1	248-666-3	25-30	Skin Sens. 1, H317 Eye Irrit. 2, H319	[1]
(Octahydro-4,7-methano-1H-indenediyl)bis (methylene) diacrylate [TRICYCLODECANEDIMETHANOL DIACRYLATE]	N/A	42594-17-2	255-901-3	5-10	Skin Sens. 1B, H317 Aquatic Chronic 2, H411	
Ethyl phenyl(2,4,6-trimethylbenzoyl) phosphinate [ETHYL (2,4,6-TRIMETHYLBENZOYL) PHENYLPHOSPHINATE]	N/A	84434-11-7	282-810-6	1-<5	Skin Sens. 1B, H317 Aquatic Chronic 2, H411	[1]
Silicon dioxide [SILICA]	N/A	7631-86-9	231-545-4	1-3	Not Classified	[2]
2,6-Di-tert-butyl-p-cresol [BHT]	N/A	128-37-0	204-881-4	<1	Aquatic Chronic 1, H410 M(Chronic)=1	[1] [2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

See section 16 for the full text of the R and H phrases declared above.

Occupational exposure limits, if available, are listed in section 8.

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] PBT-substance

[4] vPvB-substance

SECTION 4: First aid measures

4.1. Description of first aid measures	
General advice:	Remove contaminated clothing.

Kinetics Shield Matt top coat
KGPT106

Inhalation:	Remove to fresh air. If not breathing, provide artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Skin contact:	Get medical attention. Remove contaminated clothing and wash before reuse. Remove and destroy contaminated shoes. Immediately flush with plenty of water.
Eye contact:	Immediately get medical attention. Immediately wash the eyes with plenty of water for at least 15 min holding the eye open.
Ingestion:	Do not INDUCE VOMITING. Rinse mouth with water. Get medical attention.
4.2. Most important symptoms and effects, both acute and delayed	
Inhalation:	May cause nose and throat irritation. May cause respiratory irritation, causing breathing trouble, irritation, headache or nausea.
Skin contact:	Causes skin sensitisation and skin irritation. Swelling and redness of skin, pain or irritation and dermatitis.
Eye contact:	Causes serious eye irritation. Conjunctivitis, lacrimation, redness, pain or irritation, cornea damage and swelling of eyes.
Ingestion:	Harmful if swallowed, abdominal pain.
4.3. Indication of any immediate medical attention and special treatment needed	
Specific treatments:	Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

See section 11 for more detailed information on health effects and symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media	
Suitable extinguishing media:	Water spray, foam, dry chemical, carbon dioxide.
Unsuitable extinguishing media:	Full-power water jet.
5.2. Special hazards arising from the substance or mixture	
	Hazardous decomposition products may include: Carbon monoxide (CO) Carbon dioxide (CO ₂) Other unidentified organic and inorganic substances.
5.3. Advice for firefighters	
	Water may be ineffective in fighting fire. If water is used to cool closed containers to prevent pressure build-up, fog nozzles are preferred. Full protective equipment, including self-contained breathing apparatus is needed to protect fire-fighters from exposure to coating's hazardous ingredients and hazardous decomposition products. During emergency conditions, overexposure to decomposition products may cause a health hazard; symptoms may not be immediately apparent. Obtain medical attention.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures	
	Avoid contact with skin and eyes. Ensure adequate ventilation. Wear personal protective equipment. Avoid breathing vapour and avoid skin and eye contact. DO NOT ingest.
6.2. Environmental precautions	
	Do not empty into drains / surface water / ground water. Prevent further leakage or spillage. Toxic to aquatic life with long lasting effects.
6.3. Methods and material for containment and cleaning up	
	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal. Dispose of in accordance with local regulations.
6.4. Reference to other sections	
	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

Kinetics Shield Matt top coat

KGPT106





SECTION 7: Handling and storage

7.1. Precautions for safe handling	
Protective measures:	Avoid inhalation, skin and eye contact. DO NOT swallow the product.
Advice on general occupational hygiene:	<p>Good industrial hygiene practices should be observed.</p> <p>Provide sufficient air exchange and/or exhaust in work rooms.</p> <p>Wash hands before work breaks and after finishing work.</p> <p>Do not eat, drink or smoke while working.</p> <p>Take off all contaminated clothing immediately.</p> <p>Use of dispensing equipment is recommended to minimise the risk of skin or eye contact.</p> <p>See also Section 8 for additional information on hygiene measures.</p> <p>See also Section 8 for additional information on hygiene measures.</p>
7.2. Conditions for safe storage, including any incompatibilities	
Storage:	<p>Store in well-ventilated area. Keep containers (solvent resistant) closed when not in use.</p> <p>Store away from ignition sources. Store in a clean, dry area. Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.</p> <p>Empty container may retain product residues (vapour or liquid).</p>
7.3. Specific end use(s)	
Industrial sector specific solutions:	Product is for professional use only.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters	
Occupational exposure limits:	<p>Limit values are laid down throughout the EU, but each Member State establishes its own national OELs, often going beyond EU legislation. OELs are set by competent national authorities and other relevant institutions.</p> <p>United Kingdom (HSE, 2011): <i>2,6-Di-tert-butyl-p-cresol:</i> Long-term exposure limit: 8 hrs: 10 mg/m³</p> <p>Germany (TRGS-900): <i>2,6-Di-tert-butyl-p-cresol:</i> Long-term exposure limit: 8 hrs: 10 E mg/m³</p> <p><i>Silicon dioxide [SILICA]:</i> Long-term exposure limit: 8 hrs: 4 E mg/m³</p> <p>Latvia (MK 325, 2007): <i>Silicon dioxide [SILICA]:</i> Long-term exposure limit: 8 hrs: 1 mg/m³</p>
Recommended monitoring Procedures:	<p>If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.</p>
8.2. Manufacturer: Exposure controls	
Appropriate engineering Controls:	Ensure good ventilation/extraction.
Individual protection measures:	
Hygiene measures:	<p>Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.</p> <p>Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.</p>

Kinetics Shield Matt top coat KGPT106

Respiratory protection	 <p>Ensure adequate ventilation. An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area. Filter type: A</p>
Eye/face protection:	 <p>Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.</p>
Skin protection:	  <p>Chemical-resistant protective gloves (EN 374). Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374): nitrile rubber (NBR; >= 0.4 mm thickness). Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): nitrile rubber (NBR; >= 0.4 mm thickness). This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed, then the gloves should be replaced. Wear suitable protective clothing.</p>
Environmental exposure controls:	
	According to available technology.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties	
Appearance	
Physical state	Viscous liquid
Colour	Not available.
Odour	Not available.
Odour threshold	Not available.
pH at 25 °C	Not applicable.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	>100 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	Not available.
Solubility(ies)	Insoluble in water. Soluble in solvent.
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Evaporation Rate	Not available.
Explosive properties	Not available.
Oxidising properties	Not available
9.2. Other information	
Impurity	Not available

Kinetics Shield Matt top coat KGPT106

SECTION 10: Stability and reactivity

10.1. Reactivity	
	No hazardous reactions if stored and handled as prescribed/indicated.
10.2. Chemical stability	
	Stable under recommended storage conditions.
10.3. Possibility of hazardous reactions	
	Polymerization is possible.
10.4. Conditions to avoid	
	Sun-Light, un-clean conditions to avoid during storage. High temperature, localized heat sources (i.e., drum or band heaters), oxidizing conditions, freezing conditions, ultraviolet radiation, inert gas blanking.
10.5. Incompatible materials	
	Do not store with polymerization initiators including peroxides, strong oxidizing agents. Acids, bases, reducing agents. Free radical initiators, inert gases.
10.6. Hazardous decomposition products	
	Fumes produced when heated to decomposition may include: Toxic carbon monoxide, carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008				
Product:	ATE mix Oral calculation: >2000 mg/kg, not classified as acute toxic.			
Ingredients:				
Acute toxicity:	Result	Species	Dose	Exposure
Methacrylic acid, monoester with propane-1,2-diol [HYDROXYPROPYL METHACRYLATE]	LD50 Oral	Rat	>= 2 000 mg/kg bw	
	LD50 Dermal	Rabbit	> 5 000 mg/kg bw	
(Octahydro-4,7-methano-1H-indenediyl)bis (methylene) diacrylate [TRICYCLODECANEDIMETHANOL DIACRYLATE]	LD0	Rat	> 2 000 mg/kg bw	
	LD0	Rat	> 2 000 mg/kg bw	
Ethyl phenyl(2,4,6-trimethylbenzoyl) phosphinate [ETHYL (2,4,6-TRIMETHYLBENZOYL) PHENYLPHOSPHINATE]	LD50 Oral	Rat	> 5 000 mg/kg bw	
	LD50 Dermal	Rabbit	>= 2 000 mg/kg bw	
BHT (2,6-di-tert-butyl-p-cresol)	LD50 Oral	Rat	LD50 Rat oral 890 mg/kg [Sax, N.I. Dangerous Properties of Industrial Materials. 6th ed. New York, NY: Van Nostrand Reinhold, 1984., p. 426]	
Eye irritation:	Eye Irrit. 2, H319 Causes serious eye irritation.			
BIS-HPMA POLY(1,4-BUTANEDIOL)-14/IPDI COPOLYMER	Irritating to the eyes.			
Methacrylic acid, monoester with propane-1,2-diol [HYDROXYPROPYL METHACRYLATE]	Category 2B (mildly irritating to eyes) based on GHS criteria. Endpoint: Eye irritation: in vivo Guideline: Appraisal of the safety of Chemicals in foods, drugs and cosmetics by staff of the Division of Pharmacology, FDA acc. to Draize Species: Rabbit Amount applied (volume): 0.1 ml [Concentration: undiluted].			
Skin irritation/ corrosion:	Skin Irrit. 2, H315 Causes skin irritation.			
BIS-HPMA POLY(1,4-BUTANEDIOL)-14/IPDI COPOLYMER	Irritating to the skin.			
Sensitisation:	Skin Sens. 1, H317 May cause an allergic skin reaction			

**Kinetics Shield Matt top coat
KGPT106**

Methacrylic acid, monoester with propane-1,2-diol [HYDROXYPROPYL METHACRYLATE]	Sensitising. Endpoint: Skin sensitisation: in vivo (LLNA). Guideline: OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay). Species: Mouse.
(octahydro-4,7-methano-1H-indenediyl)bis(methylene) diacrylate [TRICYCLODECANEDIMETHANOL DIACRYLATE]	Indication of skin sensitising potential. Endpoint: Skin sensitisation: in vivo (non-LLNA). Guideline: OECD Guideline 406 (Skin Sensitisation). Species: Guinea pig.
Ethyl phenyl(2,4,6-trimethylbenzoyl) phosphinate [ETHYL (2,4,6-TRIMETHYLBENZOYL) PHENYLPHOSPHINATE]	Skin sensitising. Endpoint: Skin sensitisation: in vivo (LLNA). Guideline: OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay). Species: Mouse.
Repeated dose toxicity:	No known effect according to our database.
Carcinogenicity:	No known effect according to our database.
Mutagenicity:	No known effect according to our database.
Toxicity for reproduction:	No known effect according to our database.
STOT:	No known effect according to our database.
Potential acute health effects	
Eye contact:	Conjunctivitis, lacrimation, redness, pain or irritation, cornea damage and swelling of eyes.
Inhalation:	Irritation, coughing, shortness of breath, dizziness, headache or nausea.
Skin contact:	Redness, inflammation, rash, urticaria, pain or irritation and dermatitis.
Ingestion:	Gastrointestinal symptoms, such as nausea, vomiting, abdominal pain or irritation, and diarrhoea could develop.
Symptoms related to the physical, chemical and toxicological characteristics	
Eye contact:	No specific data.
Inhalation:	No specific data.
Skin contact:	No specific data.
Ingestion:	No specific data.
Delayed and immediate effects and also chronic effects from short and long term exposure	
Short term exposure:	
Potential immediate effects:	Not available.
Potential delayed effects:	Not available.
Long term exposure:	
Potential immediate effects:	Not available.
Potential delayed effects:	Not available.
Potential chronic health effects:	
Conclusion/Summary	
General	No known significant effects or critical hazards.
Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	No known significant effects or critical hazards.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.
11.2. Information on other hazards	
	Not available.

SECTION 12: Ecological information

12.1. Toxicity						
Aquatic toxicity	Aquatic Chronic 3, H412 Harmful to aquatic life with long lasting effects.					
(Octahydro-4,7-methano-1H-indenediyl)bis(methylene) diacrylate [TRICYCLODECANEDIMETHANOL DIACRYLATE]	Danio rerio	freshwater	96 h	LC50	1.65 mg/L	
	Daphnia magna	freshwater	48 h	EC50	2.36 mg/L	
	Pseudokirchneriella subcapitata	freshwater	72 h	EC50	0.71 mg/L	
	Activated sludge	freshwater	28 d	NOEC	100 mg/L	
Ethyl phenyl(2,4,6-	Danio rerio	freshwater	96 h	LC50	1.89 mg/L	

**Kinetics Shield Matt top coat
KGPT106**

trimethylbenzoyl) phosphinate [ETHYL (2,4,6- TRIMETHYLBENZOYL) PHENYLPHOSPHINATE]	Daphnia magna	freshwater	48 h	EC50	2.26 mg/L	
	Desmodesmus subspicatus	freshwater	72 h	EC50	1.01 mg/L	
	Activated sludge	freshwater	180 min	EC50	> 1 000 mg/L	
BHT (2,6-di-tert-butyl-p-cresol)	Oryzias latipes	freshwater	96 h	LC50	1.1 mg/L	
	Oryzias latipes	freshwater	30 d	NOEC	0.053 mg/L	
	Daphnia magna	freshwater	48 h	EC50	0.48 mg/L	
	Daphnia magna	freshwater	21 d	NOEC	0.069 mg/L	
	Tetrahymena pyriformis	freshwater	24 h	EC50	1.7 mg/L	
12.2. Persistence and degradability						
Product contains substances that are not readily biodegradable.						
(Octahydro-4,7-methano-1H- indenediyl)bis (methylene) diacrylate [TRICYCLODECANEDIMETHANOL DIACRYLATE]	42594-17-2	Not readily biodegradable. Degradation (O2 consumption), 28 d: 24-25%		OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)		
Ethyl phenyl(2,4,6- trimethylbenzoyl) phosphinate [ETHYL (2,4,6- TRIMETHYLBENZOYL) PHENYLPHOSPHINATE]	84434-11-7	Not readily biodegradable. Degradation (O2 consumption), 28 d: <10%		OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)		
BHT (2,6-di-tert-butyl-p-cresol)	128-37-0	Not readily biodegradable. Degradation (radiochem. meas.), 28 d: 4,7%		-		
12.3. Bioaccumulative potential						
(Octahydro-4,7-methano-1H- indenediyl)bis (methylene) diacrylate [TRICYCLODECANEDIMETHANOL DIACRYLATE]	log BCF values ranged between 0.78 and 0.79 (6.03 to 6.17 L/kg). [(Q)SAR]					
Ethyl phenyl(2,4,6- trimethylbenzoyl) phosphinate [ETHYL (2,4,6- TRIMETHYLBENZOYL) PHENYLPHOSPHINATE]	The substance has a low potential for bioaccumulation based on log Kow <=3					
BHT (2,6-di-tert-butyl-p-cresol)	The substance has a potential to bioaccumulate; however, it does not meet the criteria for being B/vB.					
12.4. Mobility in soil						
(Octahydro-4,7-methano-1H- indenediyl)bis (methylene) diacrylate [TRICYCLODECANEDIMETHANOL DIACRYLATE]	The measured Log Koc value for this substance is 3.61. Koc at 20 °C: 4 073.8					
Ethyl phenyl(2,4,6- trimethylbenzoyl) phosphinate [ETHYL (2,4,6- TRIMETHYLBENZOYL) PHENYLPHOSPHINATE]	The Log Koc of the material was determined to be 3.37 (dimensionless). Koc at 20 °C: 2 344.2					
BHT (2,6-di-tert-butyl-p-cresol)	Koc : 2.303E+004 Log Koc: 4.362					
12.5. Results of PBT and vPvB assessment						
	Regarding all available data on biotic and abiotic degradation, bioaccumulation and toxicity it can be stated that the substance does not fulfil the PBT criteria (not PBT) and not the vPvB criteria (not vPvB).					
12.6. Endocrine disrupting properties						
	2,6-Di-tert-butyl-p-cresol is under development under SEV as having endocrine disrupting properties by France. At the date of MSDS printing there was no hazard assessment outcome available to the best knowledge of the compiler of this MSDS.					
12.7. Other adverse effects						
	No known significant effects or critical hazards.					

Kinetics Shield Matt top coat KGPT106

SECTION 13: Disposal considerations

13.1. Waste treatment methods	
Product:	
Methods of disposal:	Waste must be disposed of in accordance with federal, state and local environmental control regulations. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Hazardous waste:	Within the present knowledge of the supplier, this product <u>is regarded as hazardous waste</u> , as defined by EU Directive 91/689/EEC.
European waste catalogue (EWC):	20 01 27* paint, inks, adhesives and resins containing dangerous substances
Packaging:	
Methods of disposal:	The generation of waste should be avoided or minimized wherever possible. Packaging: IBC container, plastic drum. Waste packaging should be recycled.
Special precautions:	This material and its container must be disposed of in a safe way.

SECTION 14: Transport information

This **preparation is not classified** as dangerous according to international transport regulations (ADR/RID, IMDG or ICAO/IATA).
International transport regulations:

	ADR/RID	ADN	IMDG	IATA
14.1. UN number or ID number	-	-	-	-
14.2. UN proper shipping name	-			
14.3. Transport hazard class(es)	-	-	-	-
14.4. Packing group	-	-	-	-
14.5. Environmental hazards	-	-	-	-
14.6. Special precautions for user	-	-	-	-
14.7. Maritime transport in bulk according to IMO instruments	Not applicable.			

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture	
EU Regulation (EC) No. 1907/2006 (REACH):	
Annex XIV - List of substances subject to authorization:	Substances of very high concern: None of the components are listed.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles:	Not applicable.
15.2. Chemical safety assessment	
Chemical Safety Assessment following regulation 1907/2006/EC:	A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Abbreviations and acronyms:

Kinetics Shield Matt top coat
KGPT106

Full text of abbreviations	<p>CLP: Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008] ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road RID: International Rule for Transport of Dangerous Substances by Railway IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association CAS: Chemical Abstracts Service EINECS: European Inventory of Existing Commercial Chemical Substances LC50: Median lethal concentration LD50: Median lethal dose REACH: Registration, Evaluation and Authorisation of Chemicals PBT: Persistent, bio-accumulative and toxic vPvB: Very persistent, very bio-accumulative</p>
Full text of classifications and H statements [CLP/GHS]:	<p>Skin Irrit. 2, Skin corrosion/ irritation, Hazard Category 2; H315 Causes skin irritation. Skin Sens. 1, 1B - Sensitisation — Skin, Hazard Category 1, 1B; H317 May cause an allergic skin reaction. Eye Irrit. 2 - Serious eye damage/eye irritation: Hazard Category 2; H319 Causes serious eye irritation. Aquatic Chronic 1 - Hazardous to the aquatic environment — Chronic Hazard, Category 1; H410 Very toxic to aquatic life with long lasting effects. Aquatic Chronic 2 - Hazardous to the aquatic environment — Chronic Hazard, Category 2; H411 Toxic to aquatic life with long lasting effects. Aquatic Chronic 3 - Hazardous to the aquatic environment — Chronic Hazard, Category 3; H412 Harmful to aquatic life with long lasting effects.</p>
Classification system	<p>Classification for health effects: conventional (calculation) method is used or generic/specific concentration limits: Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Classification for physico-chemical effects: No applicable. Classification for environmental effects: conventional (calculation) method is used. Aquatic Chronic 3, H412</p>
Training advice:	
	In addition to health, safety and environmental training programs for their workers, companies must ensure that workers read, understand and apply the requirements of this SDS.
Used literature:	
	European Chemical Agency's homepage (http://echa.europa.eu/). Safety data sheets of individual components.
DISCLAIMER OF LIABILITY:	
	The information in this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or method of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS/SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS/SDS information may not be applicable.

END OF SAFETY DATA SHEET